

# HYLOAD, INC. MATERIAL SAFETY DATA SHEET

## Kwik Ply Black (35/15)

### 1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

**Trade Names:** Kwik Ply Black (35/15)      **Emergency Phone Number:** 800-424-9300  
**Description:** Coal Tar Elastomeric Membrane – Self Adhered      **International Number:** 202-483-7616  
**Company Identification:** Hyload, Inc.  
9976 Rittman Rd.      **Information Number:** 330-334-5022  
Wadsworth, OH 44281      **Date Prepared:** March 24, 2005

### 2. COMPOSITION/INFORMATION ON THE HAZARDOUS COMPONENTS

<u>Hazardous Components</u>	<u>CAS No.</u>	<u>Wt. %</u>	<u>ACGIH - TLV</u>	<u>OSHA - PEL</u>	<u>Carcinogenicity</u>		
					<u>NTP</u>	<u>IARC</u>	<u>ACGIH</u>
Coal Tar Pitch	65996-93-2	10 - 15	NE	0.2 mg/m <sup>3</sup>	Yes	Yes	Yes
Basic Lead Fumarate	13698-55-0	<1	*0.15	*0.05	No	Yes	No
Asphalt	8052-42-4	10 - 15	0.5 mg/m <sup>3</sup>	NE	No	Yes	No

\* - As Lead in mg/m<sup>3</sup>

NE - Not Established/Known  
NA - Not Applicable

TLV - Threshold Limit Value

PEL - Permissible Exposure Limit

These are raw materials that have been encapsulated in the finished product. The finished product is not listed as a carcinogen by IARC, NTP, ACGIH, or OSHA

### 3. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance.....: Black**      **Odor.....: N/A**      **Physical State.....: Solid**  
**Specific Gravity.....: 1.26**      **Solubility in H<sub>2</sub>O : Insoluble**      **Density.....: 0.31 lb/ft<sup>2</sup> (50 mil thick)**  
**Boiling Point.....: NA**      **Vapor Pressure.....: NA**      **Vapor Density.....: NA**  
**Melting Point.....: NE**      **Evaporation Rate...: NA**

**Note:** The physical data presented above are typical values and not to be construed as a specification

### 4. FIRE AND EXPLOSION HAZARD

**Flash Point .....: 290F**  
**Explosive Limits: NE**

**Autoignition.....: 730F**

**EXTINGUISHING MEDIA:** Water

**FIRE FIGHTING PROCEDURES/EQUIPMENT:** Fire fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved positive pressure self-contained breathing apparatus (SCBA) and full protective clothing.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None known

### 5. REACTIVITY DATA

**CHEMICAL STABILITY:** Stable under normal conditions of use.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Temperatures in excess of 290F and sources of ignition

**INCOMPATIBILITY WITH OTHER MATERIALS:** Strong oxidizing agents

**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon, sulfur, lead, and nitrogen; amines, ammonia, chlorine compounds, and PAH's. Combustion products from polymeric compounds must be considered toxic.

---

## 6. HEALTH HAZARDS IDENTIFICATION

### HMIS RATINGS

Health - 2

Flammability - 1

Reactivity - 1

Personal Protection - B

**PRIMARY ROUTES OF EXPOSURE:** Eye, Skin, Inhalation (breathing), Ingestion (swallowing).

**EYE CONTACT:** Not expected under normal handling.

**SKIN CONTACT:** Contact with heated material may cause burns.

**INHALATION (Breathing):** Not expected under normal handling.

**INGESTION (Swallowing):** Not expected under normal handling.

**TARGET ORGANS/CHRONIC EFFECTS:** Excessive skin exposure to coal tar pitch can result in irritation, acne, folliculitis, ulcerations, benign skin growths and cancer. Chronic occupational over-exposure to coal tars may cause various cancers. However, polymer-bound compounds containing coal tar pitch minimize the possibility of this type of exposure.

**SIGNS AND SYMPTOMS OF EXPOSURE:** Not expected under normal handling. When heated, eye, respiratory and/or digestive tract irritation, and thermal burns may occur.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** Individuals with pre-existing skin disorders may be more susceptible to irritation, dermatitis, and phototoxic reactions. May also aggravate individuals with pre-existing lung and respiratory problems. Persons with a history of central nervous system (CNS) functional illness may be more susceptible to the effects when working with this product.

### EMERGENCY AND FIRST AID PROCEDURES:

**EYE CONTACT:** Flush eyes with water for at least 15 minutes. Get prompt medical attention.

**SKIN CONTACT:** For contact with molten product, do not remove contaminated clothing. Flush skin immediately with large amounts of cold water. If possible, submerge area in cold water and/or pack with ice. Get prompt medical attention. For other contact, wash effected area with nonabrasive soap and water. If irritation develops, consult a physician.

**INHALATION (Breathing):** At elevated temperatures, fumes and vapors may cause irritation to the respiratory tract. These effects are reversible upon removal from exposure. If breathing is difficult, give oxygen. If symptoms develop, seek immediate medical attention.

**INGESTION (Swallowing):** If person is conscious, first induce vomiting to prevent further absorption. Do not attempt to give anything by mouth to an unconscious person. Give oxygen if respiration is shallow. Get prompt medical attention.

---

## 7. PRECAUTIONS FOR SAFE HANDLING AND USE

**ACCIDENTAL RELEASE AND/OR SPILL MEASURES:** Sweep up, pick up or vacuum up into a dry clean container for reuse or disposal.

**WASTE DISPOSAL METHOD:** Dispose of as an industrial waste in accordance with local, state and federal regulations. Dispose of as a hazardous waste in the state of California. In Canada, dispose of the material in accordance with provincial regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store in cool, dry, well ventilated area away from heat, ignition sources, and direct sunlight. If stored outside, protect from weather.

### OTHER PRECAUTIONS:

**ENGINEERING CONTROLS/VENTILATION:** If working in a confined area, local exhaust ventilation is recommended when vapors, mists, or dusts can be released.

---

## 8. CONTROL MEASURES

**RESPIRATORY PROTECTION:** None required.

**VENTILATION:** Product is normally used outside – none required.

**PROTECTIVE GLOVES:** Cotton or similar.

**EYE PROTECTION:** Wear goggles or safety glasses.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Long-sleeved shirts are recommended.

**HYGIENIC PRACTICES:** Wash hands with hot or warm water and soap before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored.

---

## 9. REGULATORY INFORMATION

**FEDERAL:** This product is not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**SARA Title III - Section 311/312 - Hazard Categories:** N - Fire Hazard

N - Sudden Release of Pressure Hazard

N - Reactivity Hazard

Y - Immediate (Acute) Health Hazard

Y - Delayed (Chronic) Health Hazard

Ozone-Depleting chemicals - No regulated ingredients

**SARA Section 302 Extremely Hazardous Materials:** None

**SARA Section 313 Toxic Chemicals:** Coal tar pitch, Lead Carbonate

---

## 10. OTHER INFORMATION/ADDITIONAL COMMENTS

**USERS RESPONSIBILITY:** A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions - in addition to those described herein- are required. Any health hazard and safety information herein should be passed on to your customers or employees, as the case may be.

**DISCLAIMER OF LIABILITY:** The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

The ingredients listed Composition/Information on the Components Section are embedded in the product and are provided for information.

**Hyload, Inc. provides the information herein compliance with Federal hazard communication standard, 29 CFR 1910.1200, to give warning of actual and assumed hazards, and to inform of generally applicable precautions and control measures which are known to Hyload, Inc.. Hazard information is based on available scientific evidence, but is not always obtained from sources under the direction or control of Hyload, Inc.. Hyload, Inc. makes no warranty or representation that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyer's own risk. Hyload, Inc. warrants only that it has made no effort to censor other than trade secret information or to conceal hazards of its products. The data shown on these pages in no way modifies, amends or enlarges any specification or warranty.**