

HYLOAD ROOFING SYSTEM

WARRANTY CHART

CTEM SYSTEM	10-Year	15-Year	20-Year
150E Hot Applied	<p>3/16" 4' x 5' HyGlass board fastened or in asphalt</p> <p>Tape joints of HyGlass with 6" rolls of Type IV Glass felt.</p> <p>150E mopped in asphalt</p> <p>Top pour & gravel or leave smooth & weld all laps</p>	<p>3/16" 4' x 5' HyGlass board fastened or in asphalt</p> <p>2 plies of Type IV Glass in asphalt</p> <p>150E mopped in asphalt</p> <p>Top pour & gravel or leave smooth & weld all laps</p>	<p>3/16" 4' x 5' HyGlass board fastened or in asphalt</p> <p>3 plies of Type IV Glass in asphalt</p> <p>150E mopped in asphalt</p> <p>Top pour & gravel or leave smooth & weld all laps</p>
HYLOAD WS Cold Applied	<p>3/16" 4' x 5' HyGlass board fastened or in HyBond</p> <p>Tape joints with 6" rolls of HyBase SAM</p> <p>90 mil Hyload WS/hot air weld all laps</p>	<p>3/16" 4' x 5' HyGlass board fastened or in HyBond</p> <p>50 mil HyBase SAM</p> <p>75 mil Hyload WS/hot air weld all laps</p>	<p>3/16" 4' x 5' HyGlass board fastened or in HyBond</p> <p>50 mil HyBase SAM</p> <p>90 mil Hyload WS/hot air weld all laps</p>

The above are Hyload's standard guidelines regarding the type of materials that are required for each type of roof warranty. Certain variations will be allowed. Contact your Hyload Sales Specialist for details 1 800 457 4056.



HYLOAD, INC.
 9976 RITTMAN RD., WADSWORTH, OH 44281
 PH: 800 457 4056 FAX: 330 336 5512